



优钻地质材料供应有限公司 PRE-MAT DRILLING SUPPLIES PTE LTD

Co Reg. No. 199900213-K GST Reg. No. 19-9900213-K
 No. 48 Toh Guan Road East #06-107 Enterprise Hub, Singapore 608586
 Tel: (65) 6861 5323 Fax: (65) 6861 0882 Mobile: (65) 9633 1617 / (65) 9665 2712
 Email: enquiry@premat.com.sg Website: http://www.premat.com.sg

DOUBLE / TRIPLE TUBE CORE BARREL (T2 SERIES)



	Double Tube T2-101	Triple Tube T2-101(TT)
Hole Diameter	101.5 mm	101.5 mm
Core Diameter	83.6 mm	79.0 mm
OD Outer Tube	101.0 mm	101.0 mm
Bit Kerf	8.7 mm	11.0 mm
Standard Connection	NW	NW
Recommended Drill Rods	NW / NWY	NW / NWY
Impregnated Core Bit (rpm)	550 - 950	550 - 950
Weight On Bit	26 - 28 kN	26 - 28 kN
Flow Rate	93 - 147 l/min	93 - 147 l/min

	Parts List
1	Core Barrel Head
2	Outer Tube
3	Race Housing Assembly
4	Blow-out Valve Assembly (Applicable for Triple Tube)
5	Holding Tube
6	Split Tube (Applicable for Triple Tube)
7	Extension Tube
8	Core Lifter Case
9	Core Lifter Spring
10	Reamer
11	Core Bit
12	Thread Protector