

优钻地质材料供应有限公司 PRE-MAT DRILLING SUPPLIES PTE LTD

Co Reg. No. 199900213-K GST Reg. No. 19-9900213-K No. 48 Toh Guan Road East #06-107 Enterprise Hub, Singapore 608586 Tel: (65) 6861 5323 Fax: (65) 6861 0882 Mobile: (65) 9633 1617 / (65) 9665 2712 Email: enquiry@premat.com.sg Website: http://www.premat.com.sg

PM-4500-BHD

TOP HEAD DRILLING MACHINE (WITH DRIFTER)





PM-4500-BHD

SPECIFICATIONS (made in KOREA)

	HQ size		250-300 M
Drilling Capacity Dimension	NQ size		500 M
	BQ size		600 M
		are theoretical value	S Drilling denth may vary according
	These depth values are theoretical values. Drilling depth may vary according to ground conditions, equipment drilling angel, etc.		
	OALengths - transport 5.5 M		
	OAWidth		1.8 M
	OA Width OA Height - transport		2.3 M
	OA Height- mast up		7.5 M
	(Extension boom: 2 M)		7.5 141
	Weight		5.5 tons
Engine	Model		Hyundai D4DA
	Rated power		100 HP / 1800 RPM
	Fuel Capacity		180 L
	Cooling system		Water Cooling
Top Head Rotation		1st	700-1100
		2nd	600-700
	R.P.M Torque	3rd	0-250
		1st	70-50 kg-m
		2nd	93-140 kg-m
		3rd	0-420 kg-m
Feed System	Cylinder		90mm x 55mm x 3250mm
	Pull up capacity		12 tons
	Pull down capacity		6 tons
	Drill Pipe Max. Lengths		6 M
Gear Box	Gear Box can slide one side		
	Gear Box can right & left		
	Spool capacity		22 M of 12mm cable
Winch	Line Pull		3 tons
	Wireline		500 M of 6mm
Hydraulic System	General 3 Pump open loop system	Tank Capacity	160 L
		Filtration	10 micron
		Pump Model	K3V63X 2+40
		Cooling system	Air cooling
		Operating pressure	280 bar
Light & Electrical system	Control panel		Gauge floodlights
	Work		2-60 watt LED floodlights
Hydraulic Outrigger Jacks			4 EA on the outer corners of the rigs
Drill Pipe Breakout	Torque break-out		5 tons
	Double Hydraulic clamp		45mm ~ 220mm
			BW Rod or Casing, NQ-3PM,
	Centralizer		NW, HQ, NW Casing, HW
	G 1 T		Casing, PW Casing
Crawler (Rubber Type)	Crawler Type		LG4500 Combine
	Crawler speed		4 km/h
Mud Pump (3 cylinder)	FMC Triplex Pump W1122BCD		1000PSI/70kg/cm ² , 140L/min
Hydraulic Drifter	DZH 700 (= JDMD700)		

^{*}Specifications are subjected to changes without prior notice.